

electrosurgery

a compact solution for private practice



ES 120

Electrosurgical device

ES 120 is an electrocautery unit which uses high-frequency current flow for cutting and coagulating skin lesions.

Versatility of application

The unit allows to perform procedures in monopolar and bipolar modes. It excels in small surgical, gynecological, stomatological field and many others.

Automatic power regulation

The device features fully automatic adjustment of power output based on real-time monitoring of working parameters. Desired effect on tissue is repeatedly consistent in every working conditions.

Comfort

Small size and aesthetic design of ES 120 along with its reliability and easy to use features ensure the highest comfort of work.

Safety

Start-up AutoTest of generator and plugged-in accessories as well as NEM system ensures maximum safety both for an operator and a patient.

Output configuration

ES 120 is equipped with standard 3-pin monopolar and 2-pin bipolar outputs. The unit is also available with two SDS outputs.

Areas of applications:

- minor general surgery procedures (at outpatient clinics)
- dermatological procedures
- gynecological procedures
- plastic and aesthetic surgery procedures
- dental surgery procedures

Advantages of ES 120:

- small size and aesthetic design
- efficiency
- low operating costs



accessories for electrosurgical unit ES 120



100-015 Electrosurgical unit ES 120



Electrode handle

322-145 electrode handle 4mm, large, 2 switches, cable 4m, 3-pin plug



Pedal footswitch

100-302 two-pedal footswitch, cable 5m, 6-pin plug



100-301 one-pedal footswitch, cable 5m, 6-pin plug



Disposable neutral electrode EMED SAFE

812-80H hydrogel, split, for adults and children, 176x122mm, 110cm²



Disposable neutral electrode cable

380-030 L: 3m, flat plug



Bipolar cable

351-131 L: 3m, angled connector, 2-pin plug 29mm



Bipolar forceps

605-014 angled, 1mm, L: 160mm

Monopolar electrodes



520-500 Knife electrode straight, 25 x 3,5mm, handle 4mm



521-420 Ball electrode straight, 4mm, handle 4mm



521-220 Wire loop electrode, 10mm, handle 4mm



524-020 Ball electrode straight, 4mm, L: 100mm, handle 4mm



525-000 Loop electrode, 20 x 15mm, L: 120mm, handle 4mm



526-400 Tringle loop electrode, 10 x 25mm, L: 115mm, handle 4mm

EMED SP. Z O. O. SP. K. | Ryżowa 69a | 05-816 Opacz-Kolonia | Poland
Phone: +48 22 723 08 00 | email: export@emed.pl | www.emed.pl



Attention! This brochure does not replace the instructions for use! Consult instructions for use!

The information contained in this brochure is intended for health care professionals and medical equipment distributors.

Copyright © EMED All rights reserved. Any copying, distribution and publication in whole or in part without written permission of EMED is prohibited.

emed
confidence in performance

REF 2023.01.K19.EN